



IE1 STANDARD EFFICIENCY

MOTOR DATA SHEET

Motor type: **Sh71-4B**

Series: **IE1**

18-02-2026

ELECTRICAL PARAMETERS

| <i>U</i> | CONN. | <i>f</i> | <i>P</i> | | Duty | <i>I</i> | <i>n</i> | <i>T</i> | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] | | | Power factor at load [-] | | |
|----------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|------|------|
| <i>V</i> | - | Hz | <i>kW</i> | <i>HP</i> | - | A | <i>rpm</i> | <i>Nm</i> | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 230 | Δ | 50 | 0.37 | 0.50 | S1 | 2.00 | 1370 | 2.58 | 2.1 | 2.0 | 2.8 | 65.7 | 69.5 | 70.0 | 0.46 | 0.60 | 0.68 |
| 400 | Y | 50 | 0.37 | 0.50 | S1 | 1.15 | 1370 | 2.58 | 2.1 | 2.0 | 2.8 | 65.7 | 69.5 | 70.0 | 0.46 | 0.60 | 0.68 |

GENERAL DATA

| | | | |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class | - | Sound pressure level [dB] | 56 |
| Frame size | 71 | Sound power level [dB] | 63 |
| Number of poles | 4 | Terminal box position | top |
| Starting method | DOL or Y/Δ | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 62032Z |
| Frequency converter supply | yes | Bearing on ND-side | 62032Z |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | no |
| Cooling method | IC411 | Housing - material | aluminium |
| Weight (IMB3) [kg] | 5.9 | Feet - material | aluminium |
| Moment of inertia [kgm ²] | 0.00077 | Bearing shields - material | aluminium |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP 54/IP 55 | Climatic execution | U/2 |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables | 6 | Temperature sensors in bearings | no |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | on demand | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand