

## **MOTOR DATA SHEET**



02-05-2025

Motor type: 3SIE100L4A

Series: IE3

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	2.2	3.0	S1	8.0	1465	14.3	2.5	3.3	7.1	84.4	86.4	86.7	0.58	0.71	0.80
400	Y	50	2.2	3.0	S1	4.6	1465	14.3	2.5	3.3	7.1	84.4	86.4	86.7	0.58	0.71	0.80

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	55			
Frame size	100	Sound power level [dB]	67			
Number of poles	4 Terminal box position		top			
Starting method	DOL or Y/A Possibility of terminal box rotation		yes			
Insulation class	F Bearing on D-side		62062Z			
Frequency converter supply	yes	Bearing on ND-side	62062Z			
Mounting arrangement	IMB3/B5/B35/B14 Bearings regreasing		no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	27.5	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0076	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1

## CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com