

## MOTOR DATA SHEET

Motor type: **Sh80-4\_2B**

Series: **MULTI SPEED**



13-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.75	1.0	S1	2.1	1360	5.27	1.7	1.8	3.1	-	-	72.0	-	-	0.78
400	YY	50	1.0	1.27	S1	2.4	2780	3.44	1.9	2	3.8	-	-	73.0	-	-	0.82

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	-
Frame size	80	Sound power level [dB]	-
Number of poles	4 2	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62042Z
Frequency converter supply	on demand	Bearing on ND-side	62042Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	10.2	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.001874	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 54/IP 55	Climatic execution	U/2

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6		
-------------------------------	---	--	--

### STANDARDS

IEC 60034-1
-------------

### CERTIFICATES

on demand
-----------