

MOTOR DATA SHEET

Motor type: Sg112M-10



13-06-2025

Series: ABOVE 8-POLES

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.75	1.0	S1	2.3	550	13.02	2.5	2.5	3.0	42.6	52.1	71.3	0.48	0.50	0.65
690	Y	50	0.75	1.0	S1	1.4	550	13.02	2.5	2.5	3.0	42.6	52.1	71.3	0.48	0.50	0.65

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	70			
Frame size	112	Sound power level [dB]	60			
Number of poles	10	Terminal box position	top			
Starting method	DOL Possibility of terminal box rotation		yes			
Insulation class	F Bearing on D-side		6306 2Z C3			
Frequency converter supply	yes	Bearing on ND-side	6306 2Z C3			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	33	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0177	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com