

## **MOTOR DATA SHEET**

Motor type: **Sh400H10Bs** 

Series: **ABOVE 8-POLES** 



08-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ or Y	50	250	340	S1	477	593	4026	1.1	2.4	5.6	94.3	94.6	94.6	0.64	0.75	0.80
690	Δ or Y	50	250	340	S1	275	593	4026	1.1	2.4	5.6	94.3	94.6	94.6	0.64	0.75	0.80

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	76		
Frame size	400	Sound power level [dB]	-		
Number of poles	10	Terminal box position	top/ * side		
Starting method	bezpośredni. Y/D lub VSD	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	6324 C3		
Frequency converter supply	yes	Bearing on ND-side	6322 C3/* 7322 BTVP		
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	3170	Feet - material	cast iron		
Moment of inertia [kgm2]	28.5	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40 Altitude above sea level [m]		up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)			
Cable glands/inlets	2	Winding heaters	on demand			
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

