

MOTOR DATA SHEET

Motor type: 2SIE80-4B

Series: **IE2**



24-05-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	0.75	1.0	S1	3.70	1400	5.12	3.2	3.1	4.2	70.0	77.0	80.0	0.40	0.52	0.65
400	Y	50	0.75	1.0	S1	2.20	1400	5.12	3.2	3.1	4.2	70.0	77.0	80.0	0.40	0.52	0.65

GENERAL DATA							
Efficiency class	IE2	Sound pressure level [dB]	58				
Frame size	80	Sound power level [dB]	65				
Number of poles	4	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	62042Z				
Frequency converter supply	yes	Bearing on ND-side	62042Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	9.6	Feet - material	aluminium				
Moment of inertia [kgm2]	0.002089	Bearing shields - material	aluminium				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP54/IP55	Climatic execution	U/2				

ENVIRONMENTAL CONDITIONS								
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	no				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

