

MOTOR DATA SHEET

Motor type: **Sh71-6B**

Series: **IE1**



21-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	9	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	0.25	0.33	S1	1.75	860	2.77	1.7	1.7	2.4	50.9	57.1	55.0	0.50	0.64	0.79
400	Y	50	0.25	0.33	S1	1.00	860	2.77	1.7	1.7	2.4	50.9	57.1	55.0	0.50	0.64	0.79

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	50				
Frame size	71	Sound power level [dB]	57				
Number of poles	6	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	62032Z				
Frequency converter supply	yes	Bearing on ND-side	62032Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	5.8	Feet - material	aluminium				
Moment of inertia [kgm2]	0.00095	Bearing shields - material	aluminium				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP 54/IP 55	Climatic execution	U/2				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	no			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

