

## **MOTOR DATA SHEET**

Motor type: **Sh80-2B** 

Series: **IE1** 



21-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	1.1	1.5	S1	4.30	2780	3.78	2.6	2.6	5.1	75.9	77.9	77.0	0.59	0.73	0.82
400	Y	50	1.1	1.5	S1	2.50	2780	3.78	2.6	2.6	5.1	75.9	77.9	77.0	0.59	0.73	0.82

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	65			
Frame size	80	Sound power level [dB]	72			
Number of poles	2	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62042Z			
Frequency converter supply	yes	Bearing on ND-side	62042Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	9.1	Feet - material	aluminium			
Moment of inertia [kgm2]	0.001005	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP 54/IP 55	Climatic execution	U/2			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	no			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

