

## **MOTOR DATA SHEET**

Motor type: **Sh80-8B** 

Series: **IE1** 



31-10-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	0.25	0.33	S1	2.10	680	3.51	1.7	1.7	2.5	45.1	53.7	57.0	0.39	0.48	0.60
400	Y	50	0.25	0.33	S1	1.20	680	3.51	1.7	1.7	2.5	45.1	53.7	57.0	0.39	0.48	0.60

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	52				
Frame size	80	Sound power level [dB]	59				
Number of poles	8	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	62042Z				
Frequency converter supply	yes	Bearing on ND-side	62042Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	8.9	Feet - material	aluminium				
Moment of inertia [kgm2]	0.00207	Bearing shields - material	aluminium				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP 54/IP 55	Climatic execution	U/2				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	no				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

