

## **MOTOR DATA SHEET**

Motor type: **3SSIE71-4A** 

Series: Single phase IE3



21-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	F	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at lo	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	-	50	0.25	0.33	S1	1.5	1420	1.68	0.35	1.5	3.2	-	-	73.5	-	-	0.94

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	-			
Frame size	71	Sound power level [dB]	-			
Number of poles	4	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	62032Z			
Frequency converter supply	-	Bearing on ND-side	62032Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	7.7	Feet - material	aluminium			
Moment of inertia [kgm2]	0.00101	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP 54/IP 55	Climatic execution	U/2			

	ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	od -30 do +60	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY						
Number of terminals or cables	4	Temperature sensors in bearings	no			
Cable glands/inlets	1	Winding heaters	no			
Temperature sensors in winding	no	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES
on demand

ADDITIONAL INFO							
Run capacitor [mikroF/V]	20	Starting capacitor [mikroF/V]	-				

