



MOTOR DATA SHEET

Motor type: **2SIE112M4A**

Series: **IE2**

11-02-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	5.5	7.5	S1	11.5	1440	36.48	2.1	2.7	6.4	87.8	88.2	87.7	0.60	0.72	0.79
690	Y	50	5.5	7.5	S1	6.6	1440	36.48	2.1	2.7	6.4	87.8	88.2	87.7	0.60	0.72	0.79

GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	58
Frame size	112	Sound power level [dB]	70
Number of poles	4	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6306 2Z C3
Frequency converter supply	yes	Bearing on ND-side	6306 2Z C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	39.0	Feet - material	aluminium
Moment of inertia [kgm ²]	0.0115	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand