



## MOTOR DATA SHEET

Motor type: **2SIE112M6**

Series: **IE2**

23-02-2026

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	2.2	3.0	S1	5.1	955	22.0	2.3	2.7	5.9	82.0	83.1	82.3	0.52	0.66	0.75
690	Y	50	2.2	3.0	S1	3.0	955	22.0	2.3	2.7	5.9	82.0	83.1	82.3	0.52	0.66	0.75

### GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	53
Frame size	112	Sound power level [dB]	65
Number of poles	6	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63062Z
Frequency converter supply	yes	Bearing on ND-side	63062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	32.0	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.0177	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand