

MOTOR DATA SHEET

Motor type: **Sg132S-8**

Series: **IE1**



23-10-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	2.2	3.0	S1	5.5	710	29.6	2.0	2.4	4.7	75.4	78.2	78.0	0.51	0.64	0.74
690	Y	50	2.2	3.0	S1	3.2	710	29.6	2.0	2.4	4.7	75.4	78.2	78.0	0.51	0.64	0.74

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	60			
Frame size	132	Sound power level [dB]	71			
Number of poles	8	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	63082Z			
Frequency converter supply	yes	Bearing on ND-side	63082Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	53	Feet - material	cast iron			
Moment of inertia [kgm2]	0.033	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

