

MOTOR DATA SHEET

Motor type: Sg100L-8_2

Series: MULTI SPEED



08-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.5	0.7	S1	2.2	715	6.68	1.4	2.1	3.1	42	53.8	55.6	0.37	0.48	0.59
400	Y	50	2.2	2.9	S1	5.4	2910	7.22	2.1	2.4	5.9	73.8	74.4	75.8	0.56	0.68	0.77

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	68 68			
Frame size	100	Sound power level [dB]	78 78			
Number of poles	8 2	Terminal box position	top			
Starting method	DOL / DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62062Z			
Frequency converter supply	on demand	Bearing on ND-side	62062Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	26	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0065	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP 55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

