



## MOTOR DATA SHEET

Motor type: **Sg100L-8\_4A**

Series: **MULTI SPEED**

24  
68  
POLES  
MULTI  
SPEED

23-02-2026

ELECTRICAL PARAMETERS																	
<i>U</i>	CONN.	<i>f</i>	<i>P</i>		Duty	<i>I</i>	<i>n</i>	<i>T</i>	<i>TL/T</i>	<i>TB/T</i>	<i>IL/I</i>	Efficiency at load [%]			Power factor at load [-]		
<i>V</i>	-	Hz	<i>kW</i>	<i>HP</i>	-	A	<i>rpm</i>	<i>Nm</i>	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.7	0.94	S1	2.8	715	9.35	2.2	2.8	3.6	53.5	60.8	64.2	0.38	0.48	0.57
400	YY	50	1.25	1.7	S1	2.8	1425	8.38	1.7	2.5	5.05	77.5	78.9	77.7	0.68	0.79	0.86

## GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	52 64
Frame size	100	Sound power level [dB]	68 78
Number of poles	8 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62062Z
Frequency converter supply	on demand	Bearing on ND-side	62062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	23.8	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.0088	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

## ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

## ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

## STANDARDS

IEC 60034-1

## CERTIFICATES

on demand