

MOTOR DATA SHEET

Motor type: Sh71-4_2A

Series: MULTI SPEED



08-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.21	0.28	S1	0.95	1400	1.43	1.6	2	3.2	-	-	50.0	-	-	0.60
400	YY	50	0.28	0.37	S1	1.25	2800	0.96	1.6	1.8	3.2	-	-	50.0	-	-	0.70

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	-		
Frame size	71	Sound power level [dB]	-		
Number of poles	4 2	Terminal box position	top		
Starting method	DOL / DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	62032Z		
Frequency converter supply	on demand	Bearing on ND-side	62032Z		
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no		
Cooling method	IC411	Housing - material	aluminium		
Weight (IMB3) [kg]	4.9	Feet - material	aluminium		
Moment of inertia [kgm2]	0.000606	Bearing shields - material	aluminium		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP 54/IP 55	Climatic execution	U/2		

ENVIRONMENTAL CONDITIONS					
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000		
Relative humidity [%]	up to 95				

ACCESSORY				
Number of terminals or cables	6			

STANDARDS	
IEC 60034-1	

CERTIFICATES
on demand

