



## MOTOR DATA SHEET

Motor type: **Sf560H6C-E**

Series: **STANDARD EFFICIENCY**

17-02-2026

| ELECTRICAL PARAMETERS |       |          |           |           |      |          |            |           |             |             |             |                        |     |      |                          |     |      |
|-----------------------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|-----|------|--------------------------|-----|------|
| <i>U</i>              | CONN. | <i>f</i> | <i>P</i>  |           | Duty | <i>I</i> | <i>n</i>   | <i>T</i>  | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] |     |      | Power factor at load [-] |     |      |
| <i>V</i>              | -     | Hz       | <i>kW</i> | <i>HP</i> | -    | A        | <i>rpm</i> | <i>Nm</i> | -           | -           | -           | 2/4                    | 3/4 | 4/4  | 2/4                      | 3/4 | 4/4  |
| 6000                  | Y     | 50       | 1700      | 2280      | S1   | 189      | 996        | 16300     | 0.6         | 2.1         | 6.3         | -                      | -   | 97.1 | -                        | -   | 0.89 |

## GENERAL DATA

|                                       |            |                                      |                  |
|---------------------------------------|------------|--------------------------------------|------------------|
| Efficiency class                      | -          | Sound pressure level [dB]            | -                |
| Frame size                            | 560        | Sound power level [dB]               | -                |
| Number of poles                       | 6          | Terminal box position                | on right side    |
| Starting method                       | DOL        | Possibility of terminal box rotation | yes              |
| Insulation class                      | F          | Bearing on D-side                    | NU232EM1+6232MC3 |
| Frequency converter supply            | on demand  | Bearing on ND-side                   | NU226EM1         |
| Mounting arrangement                  | IM1001(B3) | Bearings regreasing                  | yes              |
| Cooling method                        | IC611      | Housing - material                   | steel            |
| Weight (IMB3) [kg]                    | 8330       | Feet - material                      | steel            |
| Moment of inertia [kgm <sup>2</sup> ] | 153        | Bearing shields - material           | steel            |
| Direction of rotation                 | CW/CCW     | Painting                             | RAL5010          |
| Degree of protection                  | IP55       | Climatic execution                   | N                |

## ENVIRONMENTAL CONDITIONS

|                          |                    |                              |            |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95           |                              |            |

## ACCESSORY

|                                |                          |                                 |                          |
|--------------------------------|--------------------------|---------------------------------|--------------------------|
| Number of terminals or cables  | 3                        | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets            | 1                        | Winding heaters                 | on demand                |
| Temperature sensors in winding | 6 x Pt100 (2 pcs./phase) | Optional accessories            | on demand                |

## STANDARDS

IEC60034-1

## CERTIFICATES

on demand