

MOTOR DATA SHEET

Motor type: **Sf710Y12**

Series: STANDARD EFFICIENCY



11-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ı	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	1250	1680	S1	156	497	24019	0.8	2	5.4	-	-	96.2	-	-	0.80

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	-		
Frame size	710	Sound power level [dB]	-		
Number of poles	12	Terminal box position	on right side		
Starting method	DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	NU238EM1+6238MC3		
Frequency converter supply	on demand	Bearing on ND-side	NU232EM1		
Mounting arrangement	IM1001(B3)	Bearings regreasing	yes		
Cooling method	IC611	Housing - material	steel		
Weight (IMB3) [kg]	11200	Feet - material	steel		
Moment of inertia [kgm2]	316	Bearing shields - material	steel		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS				
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000	
Relative humidity [%]	up to 95			

ACCESSORY				
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)	
Cable glands/inlets	1	Winding heaters	on demand	
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand	

STANDARDS	
IEC60034-1	

CERTIFICATES
on demand

