

## **MOTOR DATA SHEET**

Motor type: **Sfw710-2D** 

Series: STANDARD EFFICIENCY



11-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	3150	4223	S1	347	2987	10071	0.45	2.1	5.5	-	-	97.1	-	-	0.90

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	-		
Frame size	710	Sound power level [dB]	-		
Number of poles	2	Terminal box position	on right side		
Starting method	DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	EFZLK14-140		
Frequency converter supply	on demand	Bearing on ND-side	EFZLQ11-125		
Mounting arrangement	IM1102(B3)	Bearings regreasing	yes		
Cooling method	IC81W	Housing - material	steel		
Weight (IMB3) [kg]	9500	Feet - material	steel		
Moment of inertia [kgm2]	110	Bearing shields - material	steel		
Direction of rotation	CW or CCW (according to the order)	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS					
Ambient temperature [°C]	from +5 up to +40	Altitude above sea level [m]	up to 1000		
Relative humidity [%]	up to 95	Cooling water temperature [°C]	from +5 up to +25		

ACCESSORY					
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)		
Cable glands/inlets	1	Winding heaters	on demand		
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand		

STANDARDS	
IEC60034-1	

CERTIFICATES
on demand

