



## MOTOR DATA SHEET

Motor type: **Sh355H8C**

Series: **HIGH EFFICIENCY**

15-01-2025

<b>ELECTRICAL PARAMETERS</b>																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	200	270	S1	27.6	740	2581	1	1.7	4.2	-	-	94.2	-	-	0.74

<b>GENERAL DATA</b>			
Efficiency class	-	Sound pressure level [dB]	76
Frame size	355	Sound power level [dB]	-
Number of poles	8	Terminal box position	top/ * side
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6322MC3
Frequency converter supply	on demand	Bearing on ND-side	6322MC3
Mounting arrangement	B3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	2265	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	9.5	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

<b>ENVIRONMENTAL CONDITIONS</b>			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

<b>ACCESSORY</b>			
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand

<b>STANDARDS</b>	
IEC 60034-1	

<b>CERTIFICATES</b>	
on demand	