

MOTOR DATA SHEET

Motor type: **SIE254T4**

Series: **NEMA PREMIUM**



08-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ı	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	11	15	cont.	17.3	1775	60.1	3.5	4.4	9.7	90.7	92.0	92.4	0.76	0.84	0.88

GENERAL DATA						
Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	-			
Frame size	254	Sound power level [dB]	-			
Number of poles	4	Terminal box position	left side			
Starting method	DOL, PWS	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	63092ZC3			
Frequency converter supply	on demand	Bearing on ND-side	63092ZC3			
Mounting arrangement	IMB3/IMB35	Bearings regreasing	no			
Cooling method	IC411	Housing - material	cast iron			
Weight [Lbs]	301	Feet - material	cast iron			
Moment of inertia [Lb-Ft2]	2.89	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40 Altitude above sea level [m]		up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	12	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS	
NEMA MG-1	

CERTIFICATES	
CSA	

ADDITIONAL INFO						
NEMA design	А	NEMA code letter	К			

