

MOTOR DATA SHEET

Motor type: ESg254T-2



Series: NEMA EPACT

																0	3-05-2025
	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Efficiency at load [%]		Power	Power factor at load [-]		
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	11	15	cont.	18.2	3540		2.3	2.4	5.7	89.4	90.4	90.2			

GENERAL DATA						
Efficiency class	NEMA EPACT	Frame size	254			
Number of poles	2	Insulation class	F			
Frequency converter supply	on demand	Cooling method	IC411			
Direction of rotation	CW/CCW	Painting	RAL5010			
Climatic execution	Ν					

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Optional accessories	on demand						
STANDARDS							
NEMA MG-1							
CERTIFICATES							

CSA

ADDITIONAL INFO							
NEMA code letter	F						

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright $\ensuremath{\mathbb{C}}$ 2025 Cantoni Group www.cantonigroup.com

