

## **MOTOR DATA SHEET**

Motor type: ESg284T-8



03-05-2025

Series: NEMA EPACT

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	7.5	10	cont.	13.4	880		1.65	2.2	5.3	88.4	89.1	88.5			

GENERAL DATA						
Efficiency class	NEMA EPACT	Frame size	284			
Number of poles	8	Insulation class	F			
Frequency converter supply	on demand	Cooling method	IC411			
Direction of rotation	CW/CCW	Painting	RAL5010			
Climatic execution	Ν					

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY							
Optional accessories on demand							
STANDARDS							
NEMA MG-1							
CERTIFICATES							

ADDITIONAL INFO							
NEMA code letter	G						

CSA

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com



1 of 1