

MOTOR DATA SHEET

Motor type: ESg286TS-2



03-05-2025

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----|----|----|-------|------|------|----|------|------|------|--------|-------------|-------|-------|---------------|---------|
| U | CONN. | f | ŀ | þ | Duty | I | n | Т | TL/T | TB/T | IL/I | Effici | ency at loa | d [%] | Power | r factor at l | oad [-] |
| V | - | Hz | kW | HP | - | А | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 460 | | 60 | 22 | 30 | cont. | 35.1 | 3535 | | 2.45 | 2.9 | 5.7 | 90.5 | 91.3 | 91.0 | | | |

| GENERAL DATA | | | | | | |
|----------------------------|------------|------------------|---------|--|--|--|
| Efficiency class | NEMA EPACT | Frame size | 286 | | | |
| Number of poles | 2 | Insulation class | F | | | |
| Frequency converter supply | on demand | Cooling method | IC411 | | | |
| Direction of rotation | CW/CCW | Painting | RAL5010 | | | |
| Climatic execution | N | | | | | |

| ENVIRONMENTAL CONDITIONS | | | | | | | |
|--------------------------|-----------|------------------------------|------------|--|--|--|--|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 | | | | |
| Relative humidity [%] | up to 95 | | | | | | |

| ACCESSORY | | | | | | | |
|----------------------|-----------|--|--|--|--|--|--|
| Optional accessories | on demand | | | | | | |
| STANDARDS | | | | | | | |
| NEMA MG-1 | | | | | | | |
| CERTIFICATES | | | | | | | |

CSA

| ADDITIONAL INFO | | | | | | | |
|------------------|---|--|--|--|--|--|--|
| NEMA code letter | F | | | | | | |



Copyright $\ensuremath{\mathbb{C}}$ 2025 Cantoni Group www.cantonigroup.com

