

MOTOR DATA SHEET

Motor type: dSg160M2A-EP

Series: **GENERAL PURPOSE**



10-12-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	ŀ	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
1000	Y	50	11	15	S1	8.1	2925	36	2.1	2.5	5.7	86.2	88.3	88.5	0.80	0.87	0.89

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	70		
Frame size	160	Sound power level [dB]	80		
Number of poles	2	Terminal box position	top		
Starting method	DOL	Possibility of terminal box rotation	no		
Insulation class	F	Bearing on D-side	63092Z		
Frequency converter supply	on demand	Bearing on ND-side	63092Z		
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	145	145 Feet - material			
Moment of inertia [kgm2]	0.04	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

	ENVIRONMENTAL CONDITIONS					
Ambient temperature [°C]	from -20 up to +40 Altitude above sea level [m]		up to 1000			
Relative humidity [%]	up to 100					

ACCESSORY					
Number of terminals or cables	3	Temperature sensors in bearings	1 x bimetal (D-side)		
Cable glands/inlets	1	Winding heaters	on demand		
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand		

STANDARDS
IEC 60034-1, IEC 60079-0, IEC 60079-1

CERTIFICATES
ATEX, EAC, BiH

ADDITIONAL INFO					
Ex marking	I M2 Ex db I Mb / II2G Ex db IIA T5 Gb				

