

MOTOR DATA SHEET

Motor type: dSg90S4

Series: **GENERAL PURPOSE**



10-12-2025

							ELECTRICAL PARAMETERS										
U	CONN.	f	ŀ	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
1000	Y	50	1.1	1.5	S1	1.1	1405	7.5	2.1	2.6	4.5	71.0	74.5	75.0	0.58	0.74	0.80

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	52			
Frame size	90	Sound power level [dB]	62			
Number of poles	4	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F	Bearing on D-side	62052Z			
Frequency converter supply	on demand	Bearing on ND-side	62052Z			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	34.5	Feet - material	cast iron			
Moment of inertia [kgm2]	0.0023	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP54	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 100						

ACCESSORY					
Number of terminals or cables	3	Temperature sensors in bearings	on demand		
Cable glands/inlets	1	Winding heaters	on demand		
Temperature sensors in winding	on demand	Optional accessories	on demand		

STANDARDS				
	IEC 60034-1, IEC 60079-0, IEC 60079-1			

CERTIFICATES
ATEX, EAC, BiH

ADDITIONAL INFO					
Ex marking	I M2 Ex db I Mb / II2G Ex db IIB T5 Gb				

