



## MOTOR DATA SHEET

Motor type: **3SGf250M4z-E**

Series: **FOR MINING CONVEYOR BELT DRIVES 3SGF SERIES**

14-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
500	Y	50	65	87	S1/S4	95	1475	421	2.5	2.6	6.3	93.1	93.9	93.8	0.71	0.80	0.84

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	82
Frame size	250	Sound power level [dB]	92
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	NU 315
Frequency converter supply	on demand	Bearing on ND-side	6315 C3
Mounting arrangement	IMB35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	steel
Weight (IMB3) [kg]	590	Feet - material	steel
Moment of inertia [kgm <sup>2</sup> ]	0.61	Bearing shields - material	cast iron
Direction of rotation	CW/CWW	Painting	RAL5010
Degree of protection	IP56	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	2 x bimetallic (1pc/bearing)
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand

### STANDARDS

IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7

### CERTIFICATES

ATEX, EAC, BiH

### ADDITIONAL INFO

Ex marking	IM2 Ex db I Mb		
------------	----------------	--	--