

MOTOR DATA SHEET

Motor type: **ExSg160M-4-2GT4**

Series: INCREASED SAFETY



11-12-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	,	P	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	6	8.1	S1	11.3	1465	39.1	2	2.8	6.7	86.7	88.3	88.6	0.74	0.81	0.87

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	63			
Frame size	160	Sound power level [dB]	74			
Number of poles	4	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	63092Z			
Frequency converter supply	no	Bearing on ND-side	63092Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	105	Feet - material	cast iron			
Moment of inertia [kgm2]	0.061	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6 Temperature sensors in bearings		on demand			
Cable glands/inlets	2	Winding heaters	no			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS					
EN 60079-0, EN 60079-15					

CERTIFICATES				
	ATEX			

ADDITIONAL INFO					
tE heating time up to T4 temperature [s]	14	Ex marking	II 2G Ex eb IIC T4		

