

## **MOTOR DATA SHEET**

Motor type: **ExSh90L-4-2GT4** 

Series: INCREASED SAFETY



11-12-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	ı	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	1.1	1.5	S1	2.7	1430	7.3	2.8	3	4.8	70.6	74.9	76.0	0.58	0.70	0.78

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	56			
Frame size	90	Sound power level [dB]	66			
Number of poles	4	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62052Z			
Frequency converter supply	no	Bearing on ND-side	62052Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	16	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0028	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40 Altitude above sea level [m]		up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2	Winding heaters	no			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS					
	EN 60079-0, EN 60079-15				

CERTIFICATES
ATEX

ADDITIONAL INFO						
tE heating time up to T4 temperature [s]	10	Ex marking	II 2G Ex eb IIC T4			

