

## **MOTOR DATA SHEET**

Motor type: **(E)cSg200L2B-EP** 

Series: **FLAMEPROOF IE1** 



11-12-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	37	50	S1	64	2960	119	2.2	2.5	6.7	93.4	93.8	93.7	0.80	0.86	0.89

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	78		
Frame size	200	Sound power level [dB]	88		
Number of poles	2	Terminal box position	top		
Starting method	DOL Possibility of terminal box rotation		no		
Insulation class	F	Bearing on D-side	NU312		
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	6312C3		
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	315	Feet - material	cast iron		
Moment of inertia [kgm2]	0.18	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS					
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000		
Relative humidity [%]	up to 100				

ACCESSORY						
Number of terminals or cables	3	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO				
Ex marking	II 2G Ex db eb IIC T5 Gb / II 2G Ex db IIB T5 Gb			

