



MOTOR DATA SHEET

Motor type: **Sh355H10Cs**

Series: **ABOVE 8-POLES**

23-02-2026

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ or Y	50	200	270		400	592	3226	1.3	2.0	5.4	93.3	93.8	93.7	0.60	0.69	0.77
690	Δ or Y	50	200	270		231	592	3226	1.3	2.0	5.4	93.3	93.8	93.7	0.60	0.69	0.77

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	76
Frame size	355	Sound power level [dB]	-
Number of poles	10	Terminal box position	top/ * side
Starting method	bezpośredni. Y/D lub VSD	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6322 C3
Frequency converter supply	yes	Bearing on ND-side	6322 C3
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	2360	Feet - material	cast iron
Moment of inertia [kgm ²]	15.5	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand