

## **MOTOR DATA SHEET**

Motor type: 4SIE315L4C

Series: **IE4** 



07-06-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	200	270	S1	332	1484	1287	2.1	3.2	8.2	96.1	96.0	96.7	-	-	0.90
690	Y	50	200	270	S1	192	1484	1287	2.1	3.2	8.2	96.1	96.0	96.7	-	-	0.90

GENERAL DATA					
Efficiency class	IE4	Sound pressure level [dB]	82		
Frame size	315	Sound power level [dB]	92		
Number of poles	4	Terminal box position	top		
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	6322C3		
Frequency converter supply	yes	Bearing on ND-side	6322C3		
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	1480	Feet - material	cast iron		
Moment of inertia [kgm2]	3.66	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

