

## **MOTOR DATA SHEET**

Motor type: Ex2SIE\_80-4A

Series: INCREASED SAFETY IE3



04-12-2025

ELECTRICAL PARAMETERS																	
U	U CONN. f P		Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Efficiency at load [%]		Power factor at load [-]				
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.55	0.75	S1	1.5	1420	3.7	3.2	3.2	5.4	-	-	78.5	-	-	0.68

GENERAL DATA							
Efficiency class	IE2	Sound pressure level [dB]	-				
Frame size	80	Sound power level [dB]	-				
Number of poles	4	Terminal box position	top				
Starting method	DOL	Possibility of terminal box rotation	no				
Insulation class	F	Bearing on D-side	6204 2Z				
Frequency converter supply	no	Bearing on ND-side	6204 2Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	9.9	Feet - material	aluminium				
Moment of inertia [kgm2]	-	Bearing shields - material	aluminium				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP66	Climatic execution	NU/2				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40 Altitude above sea level [m]		up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	no			
Cable glands/inlets	2	Winding heaters	no			
Temperature sensors in winding	on demand	Optional accessories	no			

STANDARDS					
	PN-EN 60079-7:2016				

CERTIFICATES					
ATEX					

ADDITIONAL INFO						
tE heating time up to T3 temperature [s]	24	tE heating time up to T4 temperature [s]	8			
Ex marking	Ex II 2 G Ex eb IIC Tx Gb					

