

MOTOR DATA SHEET

Motor type: 3SIE200L4D

Series: **IE3**



30-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	45	60	S1	81	1481	290	2.6	3.3	7.3	93.5	94.1	94.2	0.70	0.80	0.85
690	Y	50	45	60	S1	47	1481	290	2.6	3.3	7.3	93.5	94.1	94.2	0.70	0.80	0.85

GENERAL DATA					
Efficiency class	IE3	Sound pressure level [dB]	70		
Frame size	200	Sound power level [dB]	80		
Number of poles	4	Terminal box position	top		
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	6312C3		
Frequency converter supply	yes	Bearing on ND-side	6312C3		
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	367	Feet - material	cast iron		
Moment of inertia [kgm2]	0.49	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40 Altitude above sea level [m]		up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY					
Number of terminals or cables	6	Temperature sensors in bearings	on demand		
Cable glands/inlets	2 + 1	Winding heaters	on demand		
Temperature sensors in winding	3 x PTC	Optional accessories	on demand		

STANDARDS					
IEC 60034-1					

CERTIFICATES					
on demand					

