

MOTOR DATA SHEET

Motor type: **3SIE90S4**

Series: **IE3**



30-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ı	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	1.1	1.5	S1	4.3	1450	7.2	2.3	3.5	7.2	81.8	84.0	84.1	0.56	0.69	0.77
400	Y	50	1.1	1.5	S1	2.5	1450	7.2	2.3	3.5	7.2	81.8	84.0	84.1	0.56	0.69	0.77

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	54			
Frame size	90	Sound power level [dB]	66			
Number of poles	4	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62052Z			
Frequency converter supply	yes	Bearing on ND-side	62052Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	18	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0036	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

