

MOTOR DATA SHEET

Motor type: **3SIE90S8**

Series: **IE3**



04-05-2024

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	N	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	0.37	0.50	S1	2.35	705	5	1.4	2.2	3.6	61.1	67.3	69.3	0.37	0.47	0.57
400	Y	50	0.37	0.50	S1	1.35	705	5	1.4	2.2	3.6	61.1	67.3	69.3	0.37	0.47	0.57

GENERAL DATA					
Efficiency class	IE3	Sound pressure level [dB]	45		
Frame size	90	Sound power level [dB]	55		
Number of poles	8	Terminal box position	top		
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	62052ZC3		
Frequency converter supply	yes	Bearing on ND-side	62052ZC3		
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no		
Cooling method	IC411	Housing - material	aluminium		
Weight (IMB3) [kg]	14	Feet - material	aluminium		
Moment of inertia [kgm2]	0.0026	Bearing shields - material	aluminium		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES					
on demand					

