

MOTOR DATA SHEET

Motor type: 2SIE100L4A

Series: **IE2**



30-11-2025

	ELECTRICAL PARAMETERS																	
U	CONN.	f		P)	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	factor at l	oad [-]
V	-	Hz		kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50		2.2	3.0	S1	7.9	1440	14.59	2.4	2.8	7.3	84.6	85.5	84.7	0.62	0.75	0.83
400) Y	50		2.2	3.0	S1	4.5	1440	14.59	2.4	2.8	7.3	84.6	85.5	84.7	0.62	0.75	0.83

GENERAL DATA							
Efficiency class	IE2	Sound pressure level [dB]	55				
Frame size	100	Sound power level [dB]	67				
Number of poles	4	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	62062Z				
Frequency converter supply	yes	Bearing on ND-side	62062Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	25.5	Feet - material	aluminium				
Moment of inertia [kgm2]	0.007	Bearing shields - material	aluminium				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS								
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

