

## **MOTOR DATA SHEET**

Motor type: **2SIE90S2** 

Series: **IE2** 



30-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	1.5	2.0	S1	5.7	2880	5.0	3.3	3.4	7.6	80.0	82.0	81.8	0.59	0.73	0.81
400	Y	50	1.5	2.0	S1	3.3	2880	5.0	3.3	3.4	7.6	80.0	82.0	81.8	0.59	0.73	0.81

GENERAL DATA						
Efficiency class	IE2	Sound pressure level [dB]	63			
Frame size	90	Sound power level [dB]	75			
Number of poles	2	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62052Z			
Frequency converter supply	yes	Bearing on ND-side	62052Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	13.9	Feet - material	aluminium			
Moment of inertia [kgm2]	0.0014	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

