

## **MOTOR DATA SHEET**

Motor type: 2Sg280M2z

Series: **IE1** 



30-11-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	F	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Efficiency at load [%]		Power	Power factor at load [-]		
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	110	150	S1	183	2977	353	2.2	2.5	8.3	94.0	94.9	95.1	0.78	0.85	0.91
690	Y	50	110	150	S1	106	2977	353	2.2	2.5	8.3	94.0	94.9	95.1	0.78	0.85	0.91

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	77			
Frame size	280	Sound power level [dB]	87			
Number of poles	2	Terminal box position	on right side			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6315C3			
Frequency converter supply	on demand	Bearing on ND-side	6315C3			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	585	Feet - material	cast iron			
Moment of inertia [kgm2]	0.91	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

