

MOTOR DATA SHEET



Motor type: PSg180L-2

Series: IE1

03-05-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	I	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at le	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	30	40	S1	52.8	2940	97.45	2.7	2.6	6.5	88.7	90.1	90.1	0.81	0.87	0.89
690	Y	50	30	40	S1	30.6	2940	97.45	2.7	2.6	6.5	88.7	90.1	90.1	0.81	0.87	0.89

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	78		
Frame size	180	Sound power level [dB]	88		
Number of poles	2 Terminal box position		top		
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes		
Insulation class	F Bearing on D-side		6311 2Z C3		
Frequency converter supply	yes	Bearing on ND-side	6311 2Z C3		
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	on demand		
Cooling method	IC411	Housing - material	cast iron		
Weight (IMB3) [kg]	190	Feet - material	cast iron		
Moment of inertia [kgm2]	0.095	Bearing shields - material	cast iron		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP55	Climatic execution	N		

	ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]		up to +40	Altitude above sea level [m]	up to 1000				
	Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS

IEC 60034-1

CERTIFICATES

on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com