

MOTOR DATA SHEET

Motor type: 2Sg280M12_8

Series: Multi speed



30-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Efficiency at load [%]		Power	Power factor at load [-]		
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	20	27	S1	47	492	388	2.5	2.0	4.8	-	-	88.8	-	-	0.69
400	Y	50	22	30	S1	44	742	283	1.9	2.4	5.9	-	-	90.7	-	-	0.79

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	-			
Frame size	280	Sound power level [dB]	-			
Number of poles	12 8	Terminal box position	on right side			
Starting method	DOL / DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6317P63E1			
Frequency converter supply	on demand	Bearing on ND-side	6317P63E1			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	625	Feet - material	cast iron			
Moment of inertia [kgm2]	2.05	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	2 + 1	Winding heaters	on demand				
Temperature sensors in winding	yes	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

