

MOTOR DATA SHEET

Motor type: **25g280M8_6_4**

Series: Multi speed



30-11-2025

| | ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | |
|-----|-----------------------|----|----|----|------|----|------|-----|------|------|------|--------|-------------|-------|-------|---------------|---------|
| U | CONN. | f | ı |) | Duty | I | n | Т | TL/T | TB/T | IL/I | Effici | ency at loa | d [%] | Power | r factor at l | oad [-] |
| V | - | Hz | kW | HP | - | Α | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Δ | 50 | 34 | 46 | S1 | 66 | 740 | 439 | 2.5 | 2.5 | 7.2 | - | - | 91.0 | - | - | 0.82 |
| 400 | Y | 50 | 42 | 56 | S1 | 77 | 985 | 407 | 2.1 | 2.5 | 7.5 | - | - | 90.0 | - | - | 0.87 |
| 400 | YY | 50 | 55 | 74 | S1 | 95 | 1480 | 355 | 2.5 | 2.8 | 8.5 | - | - | 89.0 | - | - | 0.94 |

| GENERAL DATA | | | | | |
|----------------------------|-----------------|--------------------------------------|---------------|--|--|
| Efficiency class | - | Sound pressure level [dB] | - | | |
| Frame size | 280 | Sound power level [dB] | - | | |
| Number of poles | 8 6 4 | Terminal box position | on right side | | |
| Starting method | DOL / DOL / DOL | Possibility of terminal box rotation | yes | | |
| Insulation class | F | Bearing on D-side | 6317P63E1 | | |
| Frequency converter supply | on demand | Bearing on ND-side | 6317P63E1 | | |
| Mounting arrangement | IMB3/B5/B35 | Bearings regreasing | yes | | |
| Cooling method | IC411 | Housing - material | cast iron | | |
| Weight (IMB3) [kg] | 635 | Feet - material | cast iron | | |
| Moment of inertia [kgm2] | 2.15 | Bearing shields - material | cast iron | | |
| Direction of rotation | CW/CCW | Painting | RAL5010 | | |
| Degree of protection | IP55 | Climatic execution | N | | |

| ENVIRONMENTAL CONDITIONS | | | | | |
|--------------------------|----------------------------------------|--|------------|--|--|
| Ambient temperature [°C] | up to +40 Altitude above sea level [m] | | up to 1000 | | |
| Relative humidity [%] | up to 95 | | | | |

| ACCESSORY | | | | |
|--------------------------------|-------|---------------------------------|-----------|--|
| Number of terminals or cables | 9 | Temperature sensors in bearings | on demand | |
| Cable glands/inlets | 2 + 1 | Winding heaters | on demand | |
| Temperature sensors in winding | yes | Optional accessories | on demand | |

| STANDARDS | |
|-------------|--|
| IEC 60034-1 | |

| CERTIFICATES |
|--------------|
| on demand |

