

## MOTOR DATA SHEET

Motor type: **2Sg315M6\_4A**

Series: **Multi speed**



15-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	62	83	S1	110	987	600	2.8	2.6	7.5	92.5	92.6	91.8	0.79	0.86	0.89
400	Δ	50	96	129	S1	160	1479	620	1.8	2.0	6.0	93.3	93.6	93.0	0.91	0.93	0.93

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	66 80
Frame size	315	Sound power level [dB]	76 90
Number of poles	6 4	Terminal box position	on right side
Starting method	DOL or Y/Δ / DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6318P63E1
Frequency converter supply	on demand	Bearing on ND-side	6318P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	880	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	2.86	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	12	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand