

MOTOR DATA SHEET

Motor type: SIE225M6_4-K

Series: Multi speed



30-11-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at lo	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	25	34	S1	52	990	241	3.0	3.1	7.8	86.7	87.7	87.5	0.63	0.74	0.79
400	Y	50	35	47	S1	62	1480	226	2.0	1.9	7.2	85.9	88.3	90.0	0.76	0.85	0.90

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	62 71				
Frame size	225	Sound power level [dB]	72 81				
Number of poles	6 4	Terminal box position	on right side				
Starting method	DOL / DOL	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	6313P63E1				
Frequency converter supply	on demand	Bearing on ND-side	6313P63E1				
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes				
Cooling method	IC411	Housing - material	cast iron				
Weight (IMB3) [kg]	365	Feet - material	cast iron				
Moment of inertia [kgm2]	0.87	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	2 + 1	Winding heaters	on demand				
Temperature sensors in winding	yes	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

