



MOTOR DATA SHEET

Motor type: **Sg132M-4_2**

Series: **Multi speed**

18-02-2026

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----------|-----------|-----------|------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|------|------|
| <i>U</i> | CONN. | <i>f</i> | <i>P</i> | | Duty | <i>I</i> | <i>n</i> | <i>T</i> | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] | | | Power factor at load [-] | | |
| <i>V</i> | - | Hz | <i>kW</i> | <i>HP</i> | - | A | <i>rpm</i> | <i>Nm</i> | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Δ | 50 | 6.0 | 8.10 | S1 | 11.8 | 1450 | 39.52 | 1.7 | 2.5 | 6.0 | 85.6 | 86.2 | 85.0 | 0.72 | 0.83 | 0.86 |
| 400 | YY | 50 | 7.2 | 9.6 | S1 | 14 | 2915 | 23.59 | 1.8 | 2.7 | 7.0 | 77.6 | 80.9 | 80.5 | 0.83 | 0.89 | 0.92 |

GENERAL DATA

| | | | |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class | - | Sound pressure level [dB] | 56 74 |
| Frame size | 132 | Sound power level [dB] | 72 72 |
| Number of poles | 4 2 | Terminal box position | top |
| Starting method | DOL / DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 63082Z |
| Frequency converter supply | on demand | Bearing on ND-side | 63082Z |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | on demand |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight (IMB3) [kg] | 70 | Feet - material | cast iron |
| Moment of inertia [kgm ²] | 0.034 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP 55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables | 6 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | on demand | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand