

MOTOR DATA SHEET

Motor type: Sh90S-4_2A

Series: Multi speed



30-11-2025

| | ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | |
|-----|-----------------------|----|-----|------|------|-----|------|------|------|------|------|--------|-------------|-------|-------|---------------|---------|
| U | CONN. | f | , | Þ | Duty | 1 | n | Т | TL/T | TB/T | IL/I | Effici | ency at loa | d [%] | Power | r factor at l | oad [-] |
| V | - | Hz | kW | HP | - | Α | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Δ | 50 | 1.1 | 1.50 | S1 | 2.8 | 1410 | 7.45 | 1.65 | 2.1 | 4.35 | 68.6 | 72.2 | 72.0 | 0.57 | 0.71 | 0.81 |
| 400 | YY | 50 | 1.4 | 1.9 | S1 | 3.1 | 2785 | 4.8 | 1.7 | 2.1 | 4.5 | 71.7 | 74.1 | 73.1 | 0.70 | 0.82 | 0.89 |

| GENERAL DATA | | | | | | | |
|----------------------------|-----------------|--------------------------------------|-----------|--|--|--|--|
| Efficiency class | - | Sound pressure level [dB] | 61 65 | | | | |
| Frame size | 90 | Sound power level [dB] | 73 79 | | | | |
| Number of poles | 4 2 | Terminal box position | top | | | | |
| Starting method | DOL / DOL | Possibility of terminal box rotation | yes | | | | |
| Insulation class | F | Bearing on D-side | 62052Z | | | | |
| Frequency converter supply | on demand | Bearing on ND-side | 62052Z | | | | |
| Mounting arrangement | IMB3/B5/B35/B14 | Bearings regreasing | no | | | | |
| Cooling method | IC411 | Housing - material | aluminium | | | | |
| Weight (IMB3) [kg] | 14 | Feet - material | aluminium | | | | |
| Moment of inertia [kgm2] | 0.0023 | Bearing shields - material | aluminium | | | | |
| Direction of rotation | CW/CCW | Painting | RAL5010 | | | | |
| Degree of protection | IP 55 | Climatic execution | N | | | | |

| ENVIRONMENTAL CONDITIONS | | | | | | | |
|--------------------------|-----------|------------------------------|------------|--|--|--|--|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 | | | | |
| Relative humidity [%] | up to 95 | | | | | | |

| ACCESSORY | | | | | | | |
|--------------------------------|-----------|---------------------------------|-----------|--|--|--|--|
| Number of terminals or cables | 6 | Temperature sensors in bearings | on demand | | | | |
| Cable glands/inlets | 1 | Winding heaters | on demand | | | | |
| Temperature sensors in winding | on demand | Optional accessories | on demand | | | | |

| STANDARDS |
|-------------|
| IEC 60034-1 |

| CERTIFICATES | |
|--------------|--|
| on demand | |

