



## MOTOR DATA SHEET

Motor type: **SIE184T4**

Series: **NEMA PREMIUM**

18-02-2026

| ELECTRICAL PARAMETERS |       |          |           |           |       |          |            |           |             |             |             |                        |      |      |                          |      |      |
|-----------------------|-------|----------|-----------|-----------|-------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|------|------|
| <i>U</i>              | CONN. | <i>f</i> | <i>P</i>  |           | Duty  | <i>I</i> | <i>n</i>   | <i>T</i>  | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
| <i>V</i>              | -     | Hz       | <i>kW</i> | <i>HP</i> | -     | A        | <i>rpm</i> | <i>Nm</i> | -           | -           | -           | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4  | 4/4  |
| 460                   | Δ     | 60       | 3.7       | 5         | cont. | 6.7      | 1770       | 20.1      | 3.5         | 3.8         | 9.1         | 87.6                   | 89.2 | 89.5 | 0.58                     | 0.71 | 0.78 |

### GENERAL DATA

|   |              |                                      |           |
|---|--------------|--------------------------------------|-----------|
| Efficiency class                        | NEMA PREMIUM | Sound pressure level [dB]            | -         |
| Frame size                              | 184          | Sound power level [dB]               | -         |
| Number of poles                         | 4            | Terminal box position                | left side |
| Starting method                         | DOL, PWS     | Possibility of terminal box rotation | yes       |
| Insulation class                        | F            | Bearing on D-side                    | 63062ZC3  |
| Frequency converter supply              | on demand    | Bearing on ND-side                   | 63062ZC3  |
| Mounting arrangement                    | IMB3/IMB35   | Bearings regreasing                  | no        |
| Cooling method                          | IC411        | Housing - material                   | cast iron |
| Weight [Lbs]                            | 108          | Feet - material                      | cast iron |
| Moment of inertia [Lb-Ft <sup>2</sup> ] | 0.34         | Bearing shields - material           | cast iron |
| Direction of rotation                   | CW/CCW       | Painting                             | RAL5010   |
| Degree of protection                    | IP55         | Climatic execution                   | N         |

### ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

### ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 12        | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 1         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

### STANDARDS

NEMA MG-1

### CERTIFICATES

CSA

### ADDITIONAL INFO

|             |   |                  |   |
|-------------|---|------------------|---|
| NEMA design | A | NEMA code letter | L |
|-------------|---|------------------|---|