



MOTOR DATA SHEET

Motor type: **SIE284T6**

Series: **NEMA PREMIUM**

11-02-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
460	Δ	60	11	15	cont.	19.5	1185	90	3.5	3.8	9.2	89.0	91.2	91.7	0.61	0.73	0.79

GENERAL DATA

Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	-
Frame size	284	Sound power level [dB]	-
Number of poles	6	Terminal box position	left side
Starting method	DOL, PWS	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63112ZC3
Frequency converter supply	on demand	Bearing on ND-side	63112ZC3
Mounting arrangement	IMB3/IMB35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight [Lbs]	371	Feet - material	cast iron
Moment of inertia [Lb-Ft ²]	5.19	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	12	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

NEMA MG-1

CERTIFICATES

CSA

ADDITIONAL INFO

NEMA design	A	NEMA code letter	L
-------------	---	------------------	---