



MOTOR DATA SHEET

Motor type: **SIE284TS2**

Series: **NEMA PREMIUM**

18-02-2026

| ELECTRICAL PARAMETERS | | | | | | | | | | | | | | | | | |
|-----------------------|-------|----------|-----------|-----------|-------|----------|------------|-----------|-------------|-------------|-------------|------------------------|------|------|--------------------------|------|------|
| <i>U</i> | CONN. | <i>f</i> | <i>P</i> | | Duty | <i>I</i> | <i>n</i> | <i>T</i> | <i>TL/T</i> | <i>TB/T</i> | <i>IL/I</i> | Efficiency at load [%] | | | Power factor at load [-] | | |
| <i>V</i> | - | Hz | <i>kW</i> | <i>HP</i> | - | A | <i>rpm</i> | <i>Nm</i> | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 460 | Δ | 60 | 18.5 | 25 | cont. | 29.5 | 3555 | 50 | 3.5 | 3 | 1 | 91.3 | 92.4 | 92.4 | 0.74 | 0.82 | 0.86 |

GENERAL DATA

| | | | |
|---|--------------|--------------------------------------|-----------|
| Efficiency class | NEMA PREMIUM | Sound pressure level [dB] | - |
| Frame size | 284 | Sound power level [dB] | - |
| Number of poles | 2 | Terminal box position | left side |
| Starting method | DOL, PWS | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 63112ZC3 |
| Frequency converter supply | on demand | Bearing on ND-side | 63112ZC3 |
| Mounting arrangement | IMB3/IMB35 | Bearings regreasing | no |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight [Lbs] | 348 | Feet - material | cast iron |
| Moment of inertia [Lb-Ft ²] | 1.72 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables | 12 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 1 | Winding heaters | on demand |
| Temperature sensors in winding | on demand | Optional accessories | on demand |

STANDARDS

NEMA MG-1

CERTIFICATES

CSA

ADDITIONAL INFO

| | | | |
|-------------|---|------------------|---|
| NEMA design | A | NEMA code letter | H |
|-------------|---|------------------|---|