

MOTOR DATA SHEET



15-06-2025

Motor type: STe324TS

Series: NEMA Epact

ELECTRICAL PARAMETERS																	
U	CONN.	f	I	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
v	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	30	40	cont.	45.6	3560	80	1.9	2.4	6.4	92.2	93.2	93.0	79.4	86.7	88.2

GENERAL DATA						
Efficiency class	NEMA EPACT	Sound pressure level [dB]	80			
Frame size	324 Sound power level [dB]		90			
Number of poles	2	Terminal box position	left side			
Starting method	DOL, PWS	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6312C3			
Frequency converter supply	on demand	Bearing on ND-side	6312C3			
Mounting arrangement	IMB3/IMB35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight [Lbs]	538	Feet - material	cast iron			
Moment of inertia [Lb-Ft2]	3.66	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	12	Temperature sensors in bearings	on demand				
Cable glands/inlets	2	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

	STANDARDS					
	NEMA MG-1					
CERTIFICATES						
	CSA					

ADDITIONAL INFO							
NEMA design	В	NEMA code letter	G				

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com

